

POWER PRUNER®

		PPF-235ES	PPT-235ES	PPT-265ES	
	Engine displacement(cm ³)	21.2	21.2	25.4	
	Dry weight (kg)	5.9	7.4	7.9	
	maximum shaft brake power (kW)	0.7	0.7	0.9	
	Overall length (mm)	2455	2670-3670	2720-3720	
	Fuel tank capacity (L)	0.45	0.45	0.50	
	Fuel consumption at maximum	0.45	0.45	0.53	
Carburett or	Carburetor Type	Diaphragm	Diaphragm	Diaphragm	
	Priming pump	○	○	○	
Ignition	Ignition system	C.D.I.	C.D.I.	C.D.I.	
	Throttle control lockout	○	○	○	
	Telescoping shaft system	-	○	○	
	Optional extension shaft(Feet)	3	4	4	
	Automatic chain oiling	○	○	○	
	Chain oil tank (L)	0.23	0.23	0.23	
	Gear reduction ratio	1.53	1.53	1.53	
	Guide bar length (inch)	10	10	12	
	Saw chain pitch (inch)	0.375	0.375	0.375	
Pysical agent	Vibration	Daily vibration exposure handle left A(8) (m/s ²)	0.5	0.8	1.4
		Daily vibration exposure handle right A(8) (m/s ²)	0.6	1.4	1.2
		Guaranteed sound power level(2000/14/EC)	108	111	111

Not all models are available in all markets throughout the world.
Also,specifications may change without notice.