

POWER SPRAYERS

		SHR-150SI	SHP-800	SHP-800S	SHP-800BS	
	Engine displacement (cm ³)	21.2	22.8	22.8	22.8	
	Dry weight*1 (kg)	5.8	9	9.4	9.5	
	Maximum shaft brake power (kW)	0.5	0.75	0.75	0.75	
	Fuel tank capacity (L)	0.5	0.75	0.75	0.75	
	Fuel consumption at maximum engine power (L/h)	0.51	0.71	0.71	0.71	
	Chemical tank capacity (L)	15	25	25	25	
	Start Assist System	i-start	-	i-start	i-start	
Carburettor	Type	Diaphragm	Circulation	Circulation	Circulation	
	Priming pump	○	○	○	○	
Ignition	Ignition system	C.D.I.	T.C.I.	T.C.I.	T.C.I.	
Pump	Type	Rotary	Double action piston			
	Maximum Pressure (kgf/cm ²)	10	25	25	25	
	Max. discharge (L/min)	8	5.8	5.8	5.8	
Pysical agent	Vibration	Daily vibration exposure handle left A(8) (m/s ²)	-	-	-	-
		Daily vibration exposure handle right A(8) (m/s ²)	0.1	-	-	-
	Sound	Guaranteed sound power level(2000/14/EC) dB(A)	105	-	-	-

*1 : Unit without spraying hose and nozzle

Not all models are available in all markets throughout the world.

Also, specifications may change without notice.